

Model	ECO WX32N
Technology	.59" 3 x TFT LCD Panels
Brightness	3200 lumens (standard) / 2250 lumens (economy)
Native Resolution	WXGA (1280 x 800)
Supported Resolution	up to 1600 x 1200 (UXGA)
Brightness Uniformity	85%<
Projection Methods	Desktop front/rear, Ceiling front/rear
Optical Offset	9:1
Contrast Ratio	4000:1
Aspect Ratio	Native 16:10; Compatible 4:3
Image Size	40 in ~ 300 in
Projection Distance	Wide: 46 in ~ 352 in / 1.174 m ~ 8.943 m Tele: 55 in ~ 422 in / 1.413 m ~ 10.737 m
Throw Ratio	1.45 ~ 1.73:1 *allow 3-5% variance on all throw ratios
Speaker	1 x 7W
Zoom Ratio	1.2:1
Digital Zoom	1/4 ~ 16
Keystone Correction	Auto +/- 30 degrees
Horizontal Scan Rate	15 ~ 100 kHz
Vertical Scan Rate	48 ~ 85 Hz
Lens Type	Manual zoom / focus
Lamp	Ushio 230W
Lamp Life	4000 hr (standard) / 6000 hr (economy)
Remote Control	Multi-function remote with battery
Noise Level	36db@1m (standard) / 32db@1m (economy)
Power Supply	100 ~ 240V AC @ 50 ~ 60Hz
Power Consumption	280W (standard) <.5W in standby mode
Safety Certifications	CE, CCC, CB, CECp, cTUVus, CE, FCC
Computer Compatibility	UXGA, SXGA, XGA, SVGA, VGA PC and Macintosh compatible
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N 480i/p, 576i/p, 720p, 1080i
Colors	1.07 billion
Inputs	S-video x 1, component x 1, video x 1 (share with component video), VGA x 2 (2nd VGA is optional in/out), 3.5mm audio x 1, RCA (L/R) x 2, HDMI x 1
Outputs	VGA x 1 (optional in/out), 3.5mm audio x 1
Service and Network Control	RS232, RJ45
Weight	6.4 lbs / 2.9 kg
Dimensions (W x H x D)	12.9 in x 9.5 in x 3.4 in / 327 mm x 241 mm x 87 mm
Operating Conditions	5°C ~ 35°C, Storage (-10°C ~ 60°C)
Security	Kensington® lock port, anti-theft bar, key pad lock
Standard Accessories	AC power cord, VGA cable, remote control with battery, user manual (CD), lens cover with string
Optional Accessories	Replacement lamp, replacement remote, OutWrite2




BOXLIGHT's ECO Series Projectors

The Eco projector series for non-interactive applications. The first of BOXLIGHT's new projector line focusing on affordable, basic classroom projection.

KEY FEATURES

- Auto keystone
- Multiple display modes
- Variable iris
- Blank screen hot key
- Freeze function
- Closed captioning
- Multiple anti-theft features
- 10 second start up
- 60 second cool down
- On-screen timer



Award Winning Technical Support 24/7/365

BOXLIGHT products come with free lifetime technical support. Speak with a hands-on, in-house, ISF Certified® technician ready to service your projector should the need arise.

